



The new degree of comfort.®

HEATING & COOLING

PR^oDUCT GUIDE



THE NEXT GENERATION OF EFFICIENCY, SUSTAINABILITY AND COMFORT



ENDEAVOR™ NEXT-LEVEL COMFORT



The all-new Rheem® Endeavor™ Line

Our Endeavor Line with Rheem Contractor App-based commissioning via Bluetooth technology, features up to 54% faster installation over other residential HVAC brands.*

*Per a 2022 MIAT Residential HVAC Competitive Time Study on base and mid-tier Endeavor Line products and commercially available competitor units of similar product tier.



Learn more about
2023 regulations at:
[Rheem.com/HVACKnowZone](https://www.rheem.com/HVACKnowZone)

RESIDENTIAL

ENDEAVOR™

IM AIR CONDITIONERS



RA18AZ

Prestige® Series

- Cooling Efficiencies up to: 20 SEER2/13 EER2
- Inverter Driven Variable Speed Compressor
- Condenser Coil Type: 3/8 in.
- PlusOne® Diagnostics & Bluetooth® Connectivity
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 54 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



RA16AZ

Classic Plus® Series

- Cooling Efficiencies up to: 17 SEER2/10.5 EER2
- Condenser Coil Type: 7mm
- PlusOne® Variable Speed Twin Rotary Compressor & Inverter Drive
- PlusOne® Diagnostics & Bluetooth® Connectivity
- PlusOne® Expanded Valve Space²
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 61 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



Limited Warranty: Conditional Unit Replacement** (Registration Required) - Ten (10) Years • Parts - Ten (10) Years



RA15AZ

Classic Plus® Series

- Cooling Efficiencies up to: 15.2 SEER2/9.8 EER2
- Condenser Coil Type: 7mm
- PlusOne® Variable Speed Twin Rotary Compressor & Inverter Drive
- PlusOne® Diagnostics & Bluetooth® Connectivity
- PlusOne® Expanded Valve Space²
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 61 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



RA14AZ

Classic® Series

- Cooling Efficiencies up to: 16 SEER2/13 EER2
- Single-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 69 dB
- Nominal Sizes: 1.5 - 5 Ton



RA13NZ

Classic® Series

- Cooling Efficiencies up to: 15.2 SEER2/12 EER2
- Single-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 68 dB
- Nominal Sizes: 1.5 - 5 Ton



Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years

IC AIR CONDITIONERS



WA15AZ

Select™ Series

- Cooling Efficiencies up to: 15.2 SEER2/9.8 EER2
- Variable Speed Twin Rotary Scroll Compressor & Inverter Drive
- Condenser Coil Type: 7mm
- Bluetooth® Connectivity
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 61 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



WA14AZ

Select™ Series

- Cooling Efficiencies up to: 16 SEER2/13 EER2
- Single-Stage Scroll Compressor
- Condenser Coil Type: 7mm
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 69 dB
- Nominal Sizes: 1.5 - 5 Ton



WA13NZ

Select™ Series

- Cooling Efficiencies up to: 15.2 SEER2/12 EER2
- Single-Stage Scroll Compressor
- Condenser Coil Type: 7mm
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 68 dB
- Nominal Sizes: 1.5 - 5 Ton



WSA14AZ

Select™ Series

- Cooling Efficiencies up to: 15.2 SEER2/12 EER2
- Single-Stage Scroll Compressor
- Condenser Coil Type: 7mm
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 74 dB
- Nominal Sizes: 1.5 - 2.5 Ton



Limited Warranty: Parts - Five (5) Years

IM HEAT PUMPS



RP18AZ

Prestige® Series

- Cooling Efficiencies up to: 20 SEER2/12.5 EER2
- Heating Efficiencies up to: 8.5 HSPF2
- Inverter Driven Variable Speed Compressor
- Condenser Coil Type: 3/8 in.
- PlusOne® Diagnostics & Bluetooth® Connectivity
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 58 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



RP16AZ

Classic Plus® Series

- Cooling Efficiencies up to: 17 SEER2/10.4 EER2
- Heating Efficiencies up to: 8.1 HSPF2
- Condenser Coil Type: 7mm
- PlusOne® Variable Speed Twin Rotary Compressor & Inverter Drive
- PlusOne® Diagnostics & Bluetooth® Connectivity
- PlusOne® Expanded Valve Space²
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 60 dB
- Nominal Sizes: 2, 3, 4 & 5 Ton



RP15AZ

Classic Plus® Series

- Cooling Efficiencies up to: 16 SEER2/11.7 EER2
- Heating Efficiencies up to: 8.1 HSPF2
- Two-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 72 dB
- Nominal Sizes: 1.5 - 5 Ton



Limited Warranty: Conditional Unit Replacement** (Registration Required) - Ten (10) Years • Parts - Ten (10) Years

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years

SOUND & SPACE CONSTRAINT SOLUTIONS: HEAT PUMPS



RP14AZ Classic® Series

- Cooling Efficiencies up to: 14.3 SEER2/10.4 EER2
- Heating Efficiencies up to: 7.6 HSPF2
- Two-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- PlusOne® Expanded Valve Space
- PlusOne® Triple Service Access
- Sound Rating¹ (as low as): 72 dB
- Nominal Sizes: 1.5 - 5 Ton



RD17AZ Universal Heat Pump Classic Plus® Series

COMING SOON



RP17*H Classic Plus® Series**

- Variable Speed Inverter-Driven Compressor
- High Efficiency DC Motor
- Rated with RHMV side discharge Air Handler
- Nominal Sizes: 2, 2.5, 3 & 4 Ton
- Matches to the side discharge air handler model RHMV***N



Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years

Limited Warranty: Parts - Ten (10) Years

iC HEAT PUMPS



RD16AZ*H Cold Climate Classic Plus® Series**

- Cooling Efficiencies up to: 18.8 SEER2/11.7 EER2
- Heating Efficiencies up to: 10.4 HSPF2
- Variable Speed Inverter Driven Compressor
- Rated down to -15° F
- Rated only with RHMVZ***N side discharge Air Handler
- Sound Rating¹ (as low as): 25 dB
- Nominal Sizes: 2.5, 3 & 4 Ton




WP15AZ Select™ Series

- Cooling Efficiencies up to: 15.2 SEER2/11.7 EER2
- Heating Efficiencies up to: 8.1 HSPF2
- Two-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 72 dB
- Nominal Sizes: 1.5 - 5 Ton

WP14AZ Select™ Series

- Cooling Efficiencies up to: 14.3 SEER2/10.4 EER2
- Heating Efficiencies up to: 7.6 HSPF2
- Two-Stage Scroll Compressor
- Condenser Coil Type: 7mm (5 ton features 3/8 in.)
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 72 dB
- Nominal Sizes: 1.5 - 5 Ton



Limited Warranty: Parts - Ten (10) Years

Limited Warranty: Parts - Five (5) Years

95+% GAS FURNACES



WSP14AZ Select™ Series

- Cooling Efficiencies up to: 14.3 SEER2/10.4 EER2
- Heating Efficiencies up to: 7.5 HSPF2
- Two-Stage Scroll Compressor
- Condenser Coil Type: 7mm
- Easily Accessible Control Box
- Sound Rating¹ (as low as): 73 dB
- Nominal Sizes: 1.5, 2 & 2.5 Ton



R98MV Prestige® Series

- 98% AFUE
- Heating Stages: Modulating
- Motor Type: Constant CFM
- PlusOne® Energy Efficiency
- PlusOne® Diagnostics
- PlusOne® Ignition System
- PlusOne® Water Management System
- Configuration: Upflow

R97MV Prestige® Series

- 97% AFUE
- Heating Stages: Modulating
- Motor Type: Constant CFM
- PlusOne® Energy Efficiency
- PlusOne® Diagnostics
- PlusOne® Ignition System
- PlusOne® Water Management System
- Configuration: Downflow/Horizontal



Limited Warranty: Parts - Five (5) Years

Limited Warranty: Conditional Unit Replacement** (Registration Required) - Limited Lifetime Heat Exchanger - Limited Lifetime • Parts - Ten (10) Years



R962V Classic Plus® Series

- 96% AFUE
- Heating Stages: Two-Stage
- Motor Type: Constant CFM
- PlusOne® Energy Efficiency
- PlusOne® Diagnostics
- PlusOne® Ignition System
- PlusOne® Water Management System
- Configuration: 4-Way Multi-Position



R951V (Ultra Low Nox) Classic® Series

- 95% AFUE
- Heating Stages: Single-Stage
- Motor Type: Constant CFM
- PlusOne® Energy Efficiency
- PlusOne® Diagnostics
- PlusOne® Ignition System
- PlusOne® Water Management System
- Configuration: 4-Way Multi-Position



R951V Classic® Series

- 95% AFUE
- Heating Stages: Single-Stage
- Motor Type: Constant CFM
- PlusOne® Energy Efficiency
- PlusOne® Diagnostics
- PlusOne® Ignition System
- PlusOne® Water Management System
- Configuration: 4-Way Multi-Position



Limited Warranty: Conditional Unit Replacement** (Registration Required) - Ten (10) Years Heat Exchanger - Limited Lifetime • Parts - Ten (10) Years

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years Heat Exchanger - Limited Lifetime

90% GAS FURNACES



- R951T Classic® Series**
- 95% AFUE
 - Heating Stages: Single-Stage
 - Motor Type: Constant Torque
 - PlusOne® Energy Efficiency
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - PlusOne® Water Management System
 - Configuration: 4-Way Multi-Position



- R921V Classic® Series**
- 92% AFUE
 - Heating Stages: Single-Stage
 - Motor Type: Constant CFM
 - PlusOne® Energy Efficiency
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - PlusOne® Water Management System
 - Configuration: 4-Way Multi-Position



- R921T Classic® Series**
- 92% AFUE
 - Heating Stages: Single-Stage
 - Motor Type: Constant Torque
 - PlusOne® Energy Efficiency
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - PlusOne® Water Management System
 - Configuration: 4-Way Multi-Position

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years
Heat Exchanger - Limited Lifetime

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years
Heat Exchanger - Limited Lifetime

80% GAS FURNACES

(Upflow/Horizontal: shown left, Downflow: shown right)



- R802V Classic Plus® Series**
- Heating Stages: Two-Stage
 - Motor Type: Constant CFM
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - Configuration: Upflow/Horizontal, Downflow



- R801V ****U (Ultra Low NOx) Classic® Series**
- Heating Stages: Single-Stage
 - Motor Type: Constant CFM
 - PlusOne® Ignition System
 - Plus One® Water Management System
 - Configuration: Upflow/Horizontal



- R801T ****U (Ultra Low NOx) Classic® Series**
- Heating Stages: Single-Stage
 - Motor Type: Constant Torque
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - Configuration: Upflow/Horizontal



Limited Warranty: Parts Ten (10) Years
Heat Exchanger - Limited Lifetime

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years
Heat Exchanger - Twenty (20) Years

AIR HANDLERS



- R801V Classic® Series**
- Heating Stages: Single-Stage
 - Motor Type: Constant CFM
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - Configuration: Upflow/Horizontal, Downflow




- R801T Classic® Series**
- Heating Stages: Single-Stage
 - Motor Type: Constant Torque
 - PlusOne® Diagnostics
 - PlusOne® Ignition System
 - Configuration: Upflow/Horizontal, Downflow



- RHMVZ**
- Constant CFM Modulating Airflow
 - Electronic Expansion Valve (EEV)
 - Aluminum Coil



- RHMVZ***N**
- Side Discharge Series
 - Constant CFM Modulating Airflow
 - Electronic Expansion Valve (EEV)
 - Aluminum Coil
 - Rated only with RD16AZ & RP17***H Heat Pumps



Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years
Heat Exchanger - Twenty (20) Years

Limited Warranty: Parts - Ten (10) Years



- RH2VZ**
- Constant CFM Two-Stage Airflow
 - Thermostatic Expansion Valve (TXV)
 - Aluminum Coil



- RH2TZ**
- Constant Torque Two-Stage Airflow
 - Thermostatic Expansion Valve (TXV)
 - Aluminum Coil

- RH1PZ**
- PSC Single-Stage Airflow
 - Thermostatic Expansion Valve (TXV)
 - Aluminum Coil

- RH3VZ**
- Constant CFM 3+ Stage Airflow
 - Thermostatic Expansion Valve (TXV)
 - Aluminum Coil



- RB2TZ**
- Constant Torque Two-Stage Airflow
 - 35" Cabinet Height

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years



RF2TZ

- Constant Torque Two-Stage Airflow
- Compact Unit Design
- Front or Bottom Return
- Aluminum Coil

RF1PZ

- PSC Single-Stage Airflow
- Compact Unit Design
- Front or Bottom Return
- Aluminum Coil

INDOOR COILS



RCFZ

- Cased & Uncased
- Aluminum A & N Coil
- Gas Furnace Application
- Thermostatic Expansion Valve (TXV) and Electronic Expansion Valve (EEV) Option

Limited Warranty: Conditional Parts** (Registration Required) - Ten (10) Years

Limited Warranty: Conditional Parts** – 10 Years

SMART THERMOSTAT



RETST800SYS

- Built in WiFi
- 4.3" LCD Touch Screen
- Works with Amazon Alexa
- Local Weather
- 5 Operating Modes
- 7-Day Programmable Schedule
- One-Touch Away
- Active Monitoring
- Integrated Air & Water Control
- Auto Changeover between Heating & Cooling



Limited Warranty: 5 Years from Installation Date If installed as part of a Rheem system, the EcoNet Control Center will be covered under the applicable product parts warranty. See product warranty card for specific details.

COMFORT FOR TODAY AND
FOR OUR FUTURE



At Rheem®, we integrate sustainable thinking into everything we do. With a dedication to doing our part to protect the environment, we make it easy for your customers to get the uptime and efficient performance they're looking for—while also doing good by our planet.

Rheem.com/Sustainability

HYDRONIC AIR HANDLERS



RW1T/RW1P

- PSC or Constant Torque Motor Options
- Hydronic Coil
- Nominal Heating Capacities (with Tankless models)

RWMV

- ECM Motor
- Modulating Operation provides superior comfort
- Hydronic Coil
- Nominal Heating Capacities (with Tankless models)

OIL FURNACES



ROCA/ROLA

- Hi-Boy Model (ROCA)
- Lo-Boy Model (ROLA)
- ECM & PSC Motor Options
- Input Rates: 85 – 175 kBTU



ROCB/ROLB

- Hi-Boy/Horizontal Model (ROCB)
- Lo-Boy Model (ROLB)
- ECM & PSC Motor Options
- Input Rates (ROCB): 70 – 154 kBTU
- Input Rates (ROLB): 70 – 105 kBTU

Limited Warranty: Parts – 5 Years • Labor – 1 Year

Limited Warranty: Parts – 5 Years • Heat Exchanger – Limited Lifetime



DUCTLESS HEAT PUMP SYSTEMS

Rheem® ductless systems offer a convenient alternative in areas of the home where traditional duct systems may not be an option—such as attics, home additions, basements or crawl spaces. Since Mini-Splits are ductless, they set up quickly, install easily and won't take up closet or attic space. Used in conjunction with a Rheem HVAC system, our high-efficiency ductless systems make it easy for you to keep spaces more comfortable and energy consumption low, while saving big on utility costs.

SINGLE-ZONE



**RIWHGZ09AJ1S/
RO1HGZ09AJ1H**
Prestige® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 33.1 SEER2/18 EER2
• 13.4 HSPF2
• Low Temp
Heating Operation

**RIWHGZ12AJ1S/
RO1HGZ12AJ1H**
Prestige® Series
• BTU: 12,000 Cooling/
16,000 Heating
• 29.4 SEER2/15.2 EER2
• 12.9 HSPF2
• Low Temp
Heating Operation

**RIWHGZ15AJ1S/
RO1HGZ15AJ1H**
Prestige® Series
• BTU: 14,500 Cooling/
18,000 Heating
• 25.3 SEER2/13.9 EER2
• 12.8 HSPF2
• Low Temp
Heating Operation

**RIWHGZ09AJ1S/
RO1HGZ09AJ1S**
Prestige® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 33.1 SEER2/18 EER2
• 13.4 HSPF2

**RIWHGZ12AJ1S/
RO1HGZ12AJ1S**
Prestige® Series
• BTU: 12,000 Cooling/
16,000 Heating
• 29.4 SEER2/15.2 EER2
• 12.9 HSPF2
• Low Temp
Heating Operation

14°F
-5°F



14°F
-15°F



**RIWHGZ15AJ1S/
RO1HGZ15AJ1S**
Prestige® Series
• BTU: 14,500 Cooling/
18,000 Heating
• 25.3 SEER2/13.9 EER2
• 12.8 HSPF2



**RIWHFZ18AJ2S/
RO1HFZ18AJ2H**
Prestige® Series
• BTU: 18,000 Cooling/
21,600 Heating
• 20 SEER2/13.3 EER2
• 10.0 HSPF2
• Low Temp
Heating Operation



**RIWHFZ24AJ2S/
RO1HFZ24AJ2H**
Prestige® Series
• BTU: 22,000 Cooling/
25,200 Heating
• 19.5 SEER2/12.5 EER2
• 10.5 HSPF2
• Low Temp
Heating Operation



**RIWHFZ30AJ2S/
RO1HFZ30AJ2H**
Prestige® Series
• BTU: 30,000 Cooling/
32,000 Heating
• 18.7 SEER2/12.5 EER2
• 10.0 HSPF2
• Low Temp
Heating Operation

-5°F
-15°F



-5°F
-15°F



14°F
-5°F



-5°F
-15°F



**RIFHFZ09AJ2S/
RO1HFZ09AJ2H**
Prestige® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 26.0 SEER2/16.0 EER2
• 11.8 HSPF2
• Low Temp
Heating Operation

**RIFHFZ12AJ2S/
RO1HFZ12AJ2H**
Prestige® Series
• BTU: 12,000 Cooling/
16,000 Heating
• 22.7 SEER2/13.1 EER2
• 11.2 HSPF2
• Low Temp
Heating Operation

**RIFHFZ15AJ2S/
RO1HFZ15AJ2H**
Prestige® Series
• BTU: 14,200 Cooling/
18,000 Heating
• 20.3 SEER2/12.5 EER2
• 10.7 HSPF2
• Low Temp
Heating Operation

**RIFHFZ09AJ2S/
RO1HFZ09AJ2S**
Prestige® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 26.0 SEER2/16.0 EER2
• 11.8 HSPF2

**RIFHFZ12AJ2S/
RO1HFZ12AJ2S**
Prestige® Series
• BTU: 12,000 Cooling/
16,000 Heating
• 22.7 SEER2/13.1 EER2
• 11.2 HSPF2

**RIFHFZ15AJ2S/
RO1HFZ15AJ2S**
Prestige® Series
• BTU: 14,200 Cooling/
18,000 Heating
• 20.3 SEER2/12.5 EER2
• 11.2 HSPF2

14°F
-15°F



14°F
-5°F



**RIWHHZ09AJ2S/
RO1HHZ09AJ2H**
Classic Plus® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 26.5 SEER2/14.3 EER2
• 12.6 HSPF2
• Low Temp
Heating Operation

**RIWHHZ12AJ2S/
RO1HHZ12AJ2H**
Classic Plus® Series
• BTU: 12,000 Cooling/
14,000 Heating
• 23.0 SEER2/12.5 EER2
• 11.1 HSPF2
• Low Temp
Heating Operation



**RIWHHZ09AJ2S/
RO1HHZ09AJ2S**
Classic Plus® Series
• BTU: 9,000 Cooling/
12,000 Heating
• 26.5 SEER2/14.3 EER2
• 12.6 HSPF2

**RIWHHZ12AJ2S/
RO1HHZ12AJ2S**
Classic Plus® Series
• BTU: 12,000 Cooling/
14,000 Heating
• 23.0 SEER2/12.5 EER2
• 11.1 HSPF2

14°F
-5°F



14°F
-5°F



Minimum Ambient Cooling Temperature: Minimum Ambient Heating Temperature:

DUCTLESS HEAT PUMPS LIMITED WARRANTY
Standard Limited Warranty:
• 5-Year Parts, 7-Year Compressor Warranty



**RIWHHZ18AJ2S/
RO1HHZ18AJ2S
Classic Plus® Series**

- BTU: 18,000 Cooling/
21,600 Heating
- 21.1 SEER2/13.0 EER2
- 11.5 HSPF2

14°F
-5°F

**RIWHHZ24AJ2S/
RO1HHZ24AJ2S
Classic Plus® Series**

- BTU: 22,000 Cooling/
25,200 Heating
- 22.5 SEER2/12.5 EER2
- 11.4 HSPF2

14°F
-5°F

**RIWHHZ24AJ2S/
RO1HHZ24AJ2H
Classic Plus® Series**

- BTU: 22,000 Cooling/
25,200 Heating
- 22.5 SEER2/12.5 EER2
- 11.4 HSPF2
- Low Temp
Heating Operation



**RIWHFZ09AA3S/
RO1Hfhz09AA3S
Classic® Series**

- BTU: 9,000 Cooling/
10,000 Heating
- 16.0 SEER2/10.8 EER2
- 9.0 HSPF2

14°F
14°F

**RIWHFZ12AA3S/
RO1Hfhz12AA3S
Classic® Series**

- BTU: 12,000 Cooling/
14,000 Heating
- 16.0 SEER2/10 EER2
- 9.0 HSPF2



14°F
14°F

**RICHHZ09AJ8S/
RO1HHZ09AJ8S
Classic® Series**

- BTU: 9,000 Cooling/
12,000 Heating
- 23.5 SEER2/13.6 EER2
- 11.8 HSPF2

14°F
-5°F

**RICHHZ12AJ8S/
RO1HHZ12AJ8S
Classic® Series**

- BTU: 12,000 Cooling/
16,000 Heating
- 23.0 SEER2/12.8 EER2
- 11.3 HSPF2

**RICHHZ18AJ8S/
RO1HHZ18AJ8S
Classic® Series**

- BTU: 17,100 Cooling/
21,600 Heating
- 21.5 SEER2/12.5 EER2
- 11.2 HSPF2



**RIMHHZ12AJ8S/
RO1HZZ12AJ8S
Classic® Series**

- BTU: 12,000 Cooling/
16,000 Heating
- 19.1 SEER2/12.5 EER2
- 10.5 HSPF2

14°F
-5°F



**RIMHHZ18AJ8S/
RO1HZZ18AJ8S
Classic® Series**

- BTU: 17,100 Cooling/
21,600 Heating
- 18.6 SEER2/11.7 EER2
- 10.0 HSPF2

14°F
-5°F



**RIMHHZ24AJ8S/
RO1HZZ24AJ8S
Classic® Series**

- BTU: 24,000 Cooling/
27,000 Heating
- 18.5 SEER2/11.7 EER2
- 10.0 HSPF2

14°F
-5°F

**RIMHHZ30AJ8S/
RO1HZZ30AJ8S
Classic® Series**

- BTU: 30,000 Cooling/
32,000 Heating
- 18.5 SEER2/10.4 EER2
- 10.0 HSPF2



**RIMHHZ36AJ8S/
RO1HZZ36AJ8S
Classic® Series**

- BTU: 36,000 Cooling/
38,000 Heating
- 18.0 SEER2/9.6 EER2
- 9.8 HSPF2

14°F
-5°F

**RIMHGZ42AJ8S/
RO1HGZ42AJ8S
Classic® Series**


- BTU: 42,000 Cooling/
47,000 Heating
- 17.3 SEER2/10.7 EER2
- 9.8 HSPF2

**RIMHGZ48AJ8S/
RO1HGZ48AJ8S
Classic® Series**

- BTU: 48,000 Cooling/
53,000 Heating
- 16.4 SEER2/9.8 EER2
- 9.0 HSPF2

Minimum Ambient Cooling Temperature: Minimum Ambient Heating Temperature:

DUCTLESS HEAT PUMPS LIMITED WARRANTY
Standard Limited Warranty:
• 5-Year Parts, 7-Year Compressor Warranty



**RIWHHZ09AJ3S/
RO1HHZ09AJ3S
Classic® Series**

- BTU: 9,000 Cooling/
10,000 Heating
- 20.5 SEER2/12.5 EER2
- 10.5 HSPF2

**RIWHHZ12AJ3S/
RO1HHZ12AJ3S
Classic® Series**

- BTU: 12,000 Cooling/
14,000 Heating
- 20.0 SEER2/11.0 EER2
- 10.5 HSPF2

**RIWHHZ18AJ3S/
RO1HHZ18AJ3S
Classic® Series**

- BTU: 18,000 Cooling/
18,000 Heating
- 20.0 SEER2/12.0 EER2
- 10.5 HSPF2

**RIWHHZ24AJ3S/
RO1HHZ24AJ3S
Classic® Series**

- BTU: 24,000 Cooling/
24,000 Heating
- 19.0 SEER2/9.2 EER2
- 9.8 HSPF2

**RIWHHZ30AJ3S/
RO1HHZ30AJ3S
Classic® Series**

- BTU: 30,000 Cooling/
30,000 Heating
- 18.0 SEER2/9.8 EER2
- 9.8 HSPF2

14°F
5°F



14°F
5°F



**RIWHHZ36AJ3S/
RO1HHZ36AJ3S
Classic® Series**

- BTU: 33,000 Cooling/
34,000 Heating
- 18.0 SEER2/8.1 EER2
- 9.6 HSPF2



**RISHHZ18AJ8S/
RO1HHZ18AJ8S
Classic® Series**

- BTU: 18,000 Cooling/
21,600 Heating
- 22.5 SEER2/12.5 EER2
- 10.6 HSPF2



**RISHHZ24AJ8S/
RO1HHZ24AJ8S
Classic® Series**

- BTU: 24,000 Cooling/
27,000 Heating
- 21.5 SEER2/12.3 EER2
- 10.5 HSPF2

14°F
5°F

0°F
14°F

**RISHHZ30AJ8S/
RO1HHZ30AJ8S
Classic® Series**

- BTU: 30,000 Cooling/
32,000 Heating
- 20.0 SEER2/10.8 EER2
- 10.5 HSPF2



**RISHHZ36AJ8S/
RO1HHZ36AJ8S
Classic® Series**

- BTU: 36,000 Cooling/
38,000 Heating
- 19.5 SEER2/9.6 EER2
- 10.0 HSPF2



**RIGHHZ18AJ8S/
RO1HHZ18AJ8S
Classic® Series**

- BTU: 18,000 Cooling/
21,600 Heating
- 23.5 SEER2/13.0 EER2
- 11.2 HSPF2

**RIGHHZ24AJ8S/
RO1HHZ24AJ8S
Classic® Series**

- BTU: 24,000 Cooling/
27,000 Heating
- 23.0 SEER2/12.6 EER2
- 11.0 HSPF2

0°F
14°F

-5°F
-5°F



**RIGHHZ30AJ8S/
RO1HHZ30AJ8S
Classic® Series**

- BTU: 30,000 Cooling/
32,000 Heating
- 21.5 SEER2/11.7 EER2
- 10.6 HSPF2

**RIGHHZ36AJ8S/
RO1HHZ36AJ8S
Classic® Series**

- BTU: 36,000 Cooling/
38,000 Heating
- 20.5 SEER2/ 10.0 EER2
- 10.2 HSPF2



**RIGHGZ42AJ8S/
RO1HGZ42AJ8S
Classic® Series**

- BTU: 42,000 Cooling/
47,000 Heating
- 19.0 SEER2/ 11.3 EER2
- 9.8 HSPF2

**RIGHGZ48AJ8S/
RO1HGZ48AJ8S
Classic® Series**

- BTU: 48,000 Cooling/
53,000 Heating
- 18.2 SEER2/ 10.1 EER2
- 9.0 HSPF2

-5°F
-5°F

Minimum Ambient Cooling Temperature:



Minimum Ambient Heating Temperature:



DUCTLESS HEAT PUMPS LIMITED WARRANTY
Standard Limited Warranty:

- 5-Year Parts, 7-Year Compressor Warranty

MULTI-ZONE DUCTLESS OPTIONS

INDOOR AIR HANDLER MODELS



RIWHHZ07AJ3S
Classic Plus® Series
• BTU: 7,000 Cooling/
8,100 Heating

RIWHHZ09AJ3S
Classic Plus® Series
• BTU: 9,000 Cooling/
10,200 Heating

RIWHHZ12AJ3S
Classic Plus® Series
• BTU: 12,000 Cooling/
13,500 Heating

RIWHHZ15AJ3S
Classic Plus® Series
• BTU: 14,000 Cooling/
16,300 Heating



RIWHHZ18AJ3S
Classic Plus® Series
• BTU: 18,000 Cooling/
20,000 Heating

RIWHHZ24AJ3S
Classic Plus® Series
• BTU: 24,000 Cooling/
27,000 Heating



RIDHHZ07AJ8S
Classic® Series
• BTU: 7,000 Cooling/
8,100 Heating

RIDHHZ09AJ8S
Classic® Series
• BTU: 9,000 Cooling/
10,200 Heating

RIDHHZ12AJ8S
Classic® Series
• BTU: 12,000 Cooling/
13,500 Heating

RIDHHZ18AJ8S
Classic® Series
• BTU: 18,000 Cooling/
20,000 Heating

RIDHHZ24AJ8S
Classic® Series
• BTU: 24,000 Cooling/
27,000 Heating



RICHHZ07AJ8S
Classic® Series
• BTU: 7,000 Cooling/
8,100 Heating

RICHHZ09AJ8S
Classic® Series
• BTU: 9,000 Cooling/
10,200 Heating

RICHHZ12AJ8S
Classic® Series
• BTU: 12,000 Cooling/
13,500 Heating

RICHHZ18AJ8S
Classic® Series
• BTU: 18,000 Cooling/
20,000 Heating



RIFHFZ09AJ2S
Classic® Series
• BTU: 9,000 Cooling/
10,200 Heating

RIFHFZ12AJ2S
Classic® Series
• BTU: 12,000 Cooling/
16,000 Heating

RIFHFZ15AJ2S
Classic® Series
• BTU: 14,200 Cooling/
18,000 Heating

OUTDOOR HEAT PUMP MODELS:

Operate up to 5 indoor units simultaneously, depending on model. Mix and Match flexibility allows you to choose the indoor unit that best fits the application.



RO2HFZ18AJ1H
Prestige® Series
• BTU: 18,000 Cooling/
22,000 Heating
• Up to 21.5 SEER2/13.5 EER2
• Up to 9.6 HSPF2

RO3HFZ24AJ1H
Prestige® Series
• BTU: 22,000 Cooling/
25,000 Heating
• Up to 20.0 SEER2/13.3 EER2
• Up to 10.0 HSPF2



RO4HFZ36AJ1H
Prestige® Series
• BTU: 35,200 Cooling/
36,400 Heating
• Up to 20.5 SEER2/13.0 EER2
• Up to 9.5 HSPF2

14°F
-15°F



RO2HFZ18AJ2S
Classic Plus® Series
• BTU: 18,000 Cooling/
22,000 Heating
• Up to 21.5 SEER2/13.5 EER2
• Up to 9.6 HSPF2

RO3HFZ24AJ2S
Classic Plus® Series
• BTU: 22,000 Cooling/
24,000 Heating
• Up to 16.0 SEER2/10.6 EER2
• Up to 8.5 HSPF2



RO4HFZ36AJ2S
Classic Plus® Series
• BTU: 35,200 Cooling/
36,400 Heating
• Up to 19.0 SEER2/10.0 EER2
• Up to 9.0 HSPF2

14°F
5°F



14°F
5°F



RO5HFZ45AJ2S
Classic Plus® Series
• BTU: 45,000 Cooling/
48,000 Heating
• Up to 20.0 SEER2/10.5 EER2
• Up to 9.2 HSPF2

14°F
5°F

Minimum Ambient Cooling Temperature: Minimum Ambient Heating Temperature:

DUCTLESS HEAT PUMPS LIMITED WARRANTY
Standard Limited Warranty:
• 5-Year Parts, 7-Year Compressor Warranty

COMMERCIAL

ENDEAVOR[®]

IR RESIDENTIAL PACKAGED GAS ELECTRIC



RGEAZR Classic[®] Series

- 1-Phase Power Options: 13.4 SEER2
- 3-Phase Power Options: 14 SEER
- Convertible Airflow
- Meets 81% AFUE Standard
- Scroll Compressor
- Microchannel Coil
- Ultra Low NOx models available
- Nominal Sizes: 2 - 5 Ton
- 2 and 2.5 Ton models only offered in 1-Phase



RGEAZS/RGEXZS Classic Plus[®] Series

COMING
SOON

Limited Warranty: (Residential Applications)
Compressor – 10 Years • Stainless Steel Heat Exchanger – Limited Lifetime • Standard Heat Exchanger – 10 Years • Conditional Parts – 10 Years

Limited Warranty: (Commercial Applications)
Compressor – 5 Years • Standard Heat Exchanger – 10 Years • Stainless Steel Heat Exchanger – 20 Years • Conditional Parts – 1 Year

PACKAGED GAS ELECTRIC

Renaissance[™] Line



RGEZCR Commercial Classic[®] Series

- Up to 13.4 SEER2/10.6 EER2
- Single-Stage Cooling
- ECM Indoor Motor
- 1-Phase and 3-Phase Power Options
- PlusOne[®] Diagnostics CoreCommand[™]
- PlusOne[®] ServiceSmart
- PlusOne[®] VelociFin[™] Heat Exchanger
- PlusOne[®] SmartShield Coil System (excluding defrost system)
- Optional PlusOne[®] HumidiDry[®]
- Nominal Sizes: 3-5 Tons

RGEZCT Commercial Classic Plus[®] Series

- 3-5 Tons: Up to 16.2 SEER2/12 EER2
- 6 Tons: 14.6 IEER/11.0 EER
- Two-Stage Cooling
- ECM Indoor Motor
- 1-Phase and 3-Phase Power Options
- PlusOne[®] Diagnostics CoreCommand[™]
- PlusOne[®] ServiceSmart
- PlusOne[®] VelociFin[™] Heat Exchanger
- PlusOne[®] SmartShield Coil System (excluding defrost system)
- Optional PlusOne[®] HumidiDry[®]
- Nominal Sizes: 3-6 Tons

Limited Warranty: (Commercial Applications) Parts – 1 Year • Compressor – 5 Years
Factory Standard Heat Exchanger – 10 Years • Stainless Steel Heat Exchanger – 20 Years

Renaissance[™] Line



RGEDZT Commercial Classic[®] Series

- Up to 14.6 IEER/11.0 EER
- Two-Stage Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne[®] Diagnostics CoreCommand[™]
- PlusOne[®] ServiceSmart
- PlusOne[®] VelociFin[™] Heat Exchanger
- PlusOne[®] SmartShield Coil System (excluding defrost system)
- Optional PlusOne[®] HumidiDry[®]
- Nominal Sizes: 7.5-12.5 Tons



RGEG2T Commercial Classic[®] Series

- Up to 14.0 IEER/10.8 EER
- Two-Stage Cooling
- Two Return Air Configuration Options
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne[®] Diagnostics CoreCommand[™]
- PlusOne[®] ServiceSmart
- PlusOne[®] VelociFin[™] Heat Exchanger
- PlusOne[®] SmartShield Coil System (excluding defrost system)
- Nominal Sizes: 15-25 Tons

Limited Warranty: (Commercial Applications) Parts – 1 Year • Compressor – 5 Years
Factory Standard Heat Exchanger – 10 Years • Stainless Steel Heat Exchanger – 20 Years

Resolute[™] Line



15, 17.5, 20 & 25 Ton

RKNL-G/-H Commercial Classic[®] Series

- Up to 14.0 IEER/10.8 EER
- 3-Phase Power Options
- Variable Frequency Drive
- RKNL-G: HumidiDry[™] models
- PlusOne[®] ClearControl[™]
- Nominal Sizes:
-G Models: 15, 20 & 25 Ton
-H Models: 15, 17.5, 20 & 25 Ton



20 Ton

15 Ton

RKRL-H Commercial Classic[®] Series

- Up to 14.0 IEER/11.6 EER
- 3-Phase Power Options
- Variable Frequency Drive
- PlusOne[®] ClearControl[™]
- Nominal Sizes: 15 & 20 Ton



RGEH5U Commercial Classic[®] Series

- Up to 14.2 IEER/9.8 EER
- Standard Single-Zone and Multi-Zone VAV
- Five-Stage Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- Convertible Airflow
- PlusOne[®] ClearControl[™]
- PlusOne[®] ServiceSmart
- PlusOne[®] Diagnostics CoreCommand[™]
- Nominal Size: 30 Tons

Limited Warranty: (Commercial Applications) Parts – 1 Year • Compressor – 5 Years
Factory Standard Heat Exchanger – 10 Years • Stainless Steel Heat Exchanger – 20 Years

IR RESIDENTIAL PACKAGED AIR CONDITIONERS



RACAZR Classic® Series

- 1-Phase Power Options: 13.4 SEER2
- 3-Phase Power Options: 14 SEER
- Convertible Airflow
- Scroll Compressor
- Microchannel Coils
- Nominal Sizes: 2 - 5 Ton
- 2 and 2.5 Ton models only offered in 1-Phase



RACAZS/RACXZS Classic Plus® Series

- 1-Phase Power Options: 15.2 SEER2/11.5 EER2
- 3-Phase Power Options: 16 SEER/12 EER2
- Convertible Airflow
- Two-Stage Scroll Compressor
- Microchannel Coils
- Nominal Sizes: 2 - 5 Tons



RACBZR Classic® Series

- 13.4 SEER2
- 1-Phase Power Options
- Scroll Compressor
- Microchannel Coils
- Nominal Sizes: 2-5 Ton

Limited Warranty: (Residential Applications) Compressor – 10 Years • Conditional Parts – 10 Years
Limited Warranty: (Commercial Applications) Compressor – 5 Years • Conditional Parts – 1 Year

PACKAGED AIR CONDITIONERS

Renaissance™ Line



RACCZR Commercial Classic® Series

- Up to 13.4 SEER2/10.6 EER2
- Single-Stage Cooling
- ECM Indoor Motor
- 1-Phase and 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System (excluding defrost system)
- Optional PlusOne® HumidiDry®
- Nominal Sizes: 3-5 Tons

RACCZT Commercial Classic Plus® Series

- 3-5 Tons: Up to 16.2 SEER2/12 EER2
- 6 Tons: 14.8 IEER/11.2 EER
- Two-Stage Cooling
- ECM Indoor Motor
- 1-Phase and 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System (excluding defrost system)
- Optional PlusOne® HumidiDry®
- Nominal Sizes: 3-6 Tons

Limited Warranty: (Commercial Applications) Compressor - 5 Years • Parts - 1 Year

Renaissance™ Line



RACDZT Commercial Classic® Series

- Up to 14.8 IEER/11.2 EER
- Two-Stage Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System (excluding defrost system)
- Optional PlusOne® HumidiDry®
- Nominal Sizes: 7.5-12.5 Tons



RACG2T Commercial Classic® Series

- Up to 14.2 IEER/11 EER
- Two-Stage Cooling
- Two Return Air Configuration Options
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System (excluding defrost system)
- Nominal Sizes: 15-25 Tons

Limited Warranty: (Commercial Applications) Compressor – 5 Years • Parts – 1 Year

Resolute™ Line



RLNL-G/-H Commercial Classic® Series

- Up to 14.2 IEER/11.0 EER
- 3-Phase Power Options
- Variable Frequency Drive
- RLNL-G: HumidiDry™ models
- PlusOne® ClearControl™
- Nominal Sizes:
 - G Models: 15, 20 & 25 Ton
 - H Models: 15, 17.5, 20 & 25 Ton



RLRL-H Commercial Classic® Series

- Up to 14.2 IEER/11.6 EER
- 3-Phase Power Options
- Variable Frequency Drive
- PlusOne® ClearControl™
- Nominal Sizes: 15 & 20 Ton



RACH5U Commercial Classic® Series

- Up to 14.2 IEER/10.5 EER
- Standard Single-Zone and Multi-Zone VAV
- Five-Stage Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- Convertible Airflow
- PlusOne® ClearControl™
- PlusOne® ServiceSmart
- PlusOne® Diagnostics CoreCommand™
- Nominal Size: 30 Tons

Limited Warranty: (Commercial Applications) Compressor – 5 Years • Parts – 1 Year

IR RESIDENTIAL PACKAGED HEAT PUMPS



**RHPAZR/RHPXZR
Classic® Series**

- 1-Phase Power Options: 13.4 SEER2/6.7 HSPF2
- 3-Phase Power Options: 14 SEER/8 HSPF
- Convertible Airflow
- Scroll Compressor
- Microchannel Indoor Coils
- Nominal Sizes: 2 - 5 Ton
- 2 and 2.5 Ton models only offered in 1-Phase



**RHPAZS/RHPXZS
Classic Plus® Series**

**COMING
SOON**



**RHPBZR
Classic® Series**

- 13.4 SEER2
- 1-Phase Power Options
- Scroll Compressor
- Nominal Sizes: 2 - 5 Ton

Limited Warranty: (Residential Applications) Compressor – 10 Years • Conditional Parts – 10 Years
Limited Warranty: (Commercial Applications) Compressor – 5 Years • Conditional Parts – 1 Year

PACKAGED HEAT PUMPS

Renaissance™ Line



**RHPCZR
Commercial Classic® Series**

- Up to 13.4 SEER2/10.6 EER2
- Up to 6.7 HSPF2
- Single-Stage Cooling
- ECM Indoor Motor
- 1-Phase and 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System
- Nominal Sizes: 3-5 Tons

**RHPCZT
Commercial Classic® Series**

- Up to 14.1 IEER/11.0 EER
- Up to 3.4 COP
- Two-Stage Cooling
- ECM Indoor Motor
- 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System
- Nominal Size: 6 Tons

Limited Warranty: Compressor – 5 Years (Commercial Applications) • Parts – 1 Year (Commercial Applications)

Renaissance™ Line

Resolute™ Line



**RHPDZT
Commercial Classic® Series**

- Up to 14.1 IEER/11.0 EER
- Up to 3.4 COP
- Two-Stage Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne® Diagnostics CoreCommand™
- PlusOne® ServiceSmart
- PlusOne® SmartShield Coil System
- Nominal Sizes: 7.5-10 Tons



**RHPH2T
Commercial Classic® Series**

- Up to 13.5 IEER/10.6 EER
- Up to 3.3 COP
- Two-Stage Heating and Cooling
- Variable Frequency Drive
- 3-Phase Power Options
- PlusOne® ServiceSmart
- Nominal Sizes: 15-20 Tons

Limited Warranty:
Compressor – 5 Years (Commercial Applications)
Parts – 1 Year (Commercial Applications)

Limited Warranty:
Compressor – 5 Years (Commercial Applications)
Parts – 1 Year (Commercial Applications)

COMMERCIAL SPLIT AIR CONDITIONERS

COMMERCIAL SPLIT HEAT PUMPS



6.5 & 7.5 Ton



10, 12.5, 15 & 20 Ton

**RACL
Commercial
Classic® Series**

- Up to 11.2 EER/14.8 IEER
- For use with matching RHCLA Models
- 3-Phase Power Options
- Scroll Compressor
- Nominal Sizes: 6.5, 7.5, 10, 12.5, 15 & 20 Ton



**RPCL
Commercial
Classic® Series**

- 3-Phase Power Options
- Scroll Compressor
- Nominal Sizes: 7.5 & 10 Ton

Limited Warranty:
Compressor – 5 Years
Parts – 1 Year

Limited Warranty:
Compressor – 5 Years
Parts – 1 Year

COMMERCIAL SPLIT AIR HANDLERS



RHCLP Commercial Classic® Series

- Standard VFD
- 3-Phase Power Options
- Horizontal or Vertical Airflow
- For use with matching RPCL models
- Heat Pump Operation
- Nominal Sizes: 7.5 - 10 Ton

RHCLA Commercial Classic® Series

- Standard VFD
- 3-Phase Power Options
- Horizontal or Vertical Airflow
- For use with matching RACL models
- Cooling Operation
- Nominal Sizes: 7.5 - 20 Ton

Limited Warranty: Parts – 1 Year

COMMERCIAL INDOOR AIR QUALITY (IAQ)



Dedicated Outdoor Air Systems (DOAS)

- Up to 21.3 IEER
- Available in G/E, A/C, and Heat Pump Configurations
- Nominal Sizes: 5-50 Tons
- Nominal Airflow: 500-15,000 CFM



RXRX-UV

- UV-C Light Kits for Renaissance products



RXMF

- MERV 8 and MERV 13 Filter Media Kits

ROOF CURB



RXSG

- 2-5 Ton

RXKG

- Compatible with Renaissance 3-12.5 ton units and Resolute 15-30 ton units

RXRX

- Compatible with Renaissance 15-25 ton units

COMMERCIAL COILS



RCCL

- Dual Furnace Coils
- Nominal Sizes: 6.5, 7.5 & 10 Ton

Limited Warranty: Parts – 1 Year

COMMERCIAL FACTORY & FIELD OPTIONS



HAIL GUARD

- Provides coil protection from hail or vandalism

ADDITIONAL OPTIONS:

- High & Low Pressure Switch Kit
- Low Ambient Control Kit
- Freeze-Stat Kit



ECONOMIZER

- Single Enthalpy (Outdoor)
- Optional Field-Installed Power Exhaust
- Optional Field-Installed Carbon Dioxide Detector
- Optional Field-Installed Dual Enthalpy



STAINLESS STEEL HEAT EXCHANGER

- Limited Lifetime Warranty in Residential Applications
- 20-Year Warranty in Commercial Applications



UNWIRED CONVENIENCE OUTLET

- 120 VAC
- 15 amp
- GFCI



UNFUSED SERVICE DISCONNECT

- Provides convenient disconnect access



Helping You Live Both Comfortably and Sustainably

Many Rheem products have sustainability features, but the products that have earned our Sustainability Standout Seal are among the best of the best. We created the Seal to help you more easily find the products that save energy, save money and save the planet.



Notes: *ENERGY STAR® compliant in certain matched systems. See applicable specification sheets on Rheem.com for further details. Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR requirements. Ask your contractor for details or visit www.energystar.gov.



With the Rheem® Contractor App (or EcoNet® App), built-in Bluetooth® technology makes advanced set-up, monitoring, troubleshooting and repairing the product easier than ever before.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Rheem® is under license.



DUAL FUEL SYSTEM: Combines the advantages of the electric heat pump and gas furnace to deliver the highest level of comfort at the lowest economical price.

Key Features & Benefits:

- Flexible energy consumption choices
- Cost savings on utility bills
- Easy replacement system
- Optimized heating potential

¹Based on Internal R&D Testing, May 2022. Sound levels are also dependent on proper installation and location of outdoor product.

²Does not apply to 2 and 3 ton models.

Limited Warranty Information:

** Specific conditions apply and online registration is required. Refer to manufacturer product warranty card for specific details.

ClearControl™

ClearControl™

Models are compatible with standard 24-Volt Programmable Thermostats.

Key Features & Benefits:

- System Failure Protection
 - Faster & Simpler Service Calls
 - Greater Application Optimization
 - Intelligent Troubleshooting
 - Energy Cost Savings
 - BAS Compatible (Modbus®, BACnet® or LonWorks™)
- additional accessory may be required



Rheem Heating & Cooling



5600 Old Greenwood Road, Fort Smith, AR 72908
Rheem manufactures residential & commercial heating, cooling and water heating products. "In keeping with its policy of continued progress and product improvement, Rheem reserves the right to make changes without notice."